

FLOS

■ F6602030 Black

Taccia

Designed by Achille and Pier Giacomo Castiglioni, 1962


28W - N/Dlm - 2700K



Table lamp providing indirect and reflected light. Reflector in painted aluminium, gloss white on the outside and matt white on the inside. Directionable diffuser in transparent mouth-blown glass. Body in matt black. silver anodized or bronze anodized aluminium. Base in nickel-plated metal. Electric cable of useful length 220 cm, with dimmer switch for ON/OFF and adjustment of the light flow between 10-100%. Plug-in power supply with interchangeable plugs.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8059607006689
Mounting	Table floor
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Power (W)	28
System flux (lm)	N/D

Physical


Colour	Black
Cord length (mm)	2200
Net weight (kg)	10.74
Package volume (m3)	0.18
IP	20

Download


Mounting instructions	Download PDF
Mounting instructions	Download PDF
Spare Parts	Download PDF

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/48
Driver	Remote included
Dimming type	Electronic 48V
Cord length (mm)	2200
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

Spare Parts



F6510000
Taccia transparent diffuser & reflector



F6608030
Black base



RF00780
White reflector



RF3320400
Black plug assembly kit & 48V driver



RF6608100
Jack plug with cable and push dimmer

FLOS

■ F6604030 Black

Taccia Small

Designed by Achille and Pier Giacomo Castiglioni, 1962


16W - N/Dlm - 2700K



Table lamp providing indirect and reflected light. Reflector in painted aluminium, gloss white on the outside and matt white on the inside. Directionable diffuser in transparent blown glass. Body in matt black or naturally anodized extruded aluminium. Base in nickel-plated ABS+PC. Electric cable of useful length 190 cm, with dimmer switch for ON/OFF and adjustment of the light flow between 10-100%. Plug-in power supply with interchangeable plugs.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8059607006740
Mounting	Table floor
Environment	Indoor dry location
Light source type	LED
LED type	LED array
Lamp holder	COB LED
Power (W)	16
System flux (lm)	N/D

Physical


Colour	Black
Cord length (mm)	1900
Net weight (kg)	4.25
Package volume (m3)	0.11
IP	20

Download


Mounting instructions	↓ PDF
Mounting instructions	↓ PDF
Spare Parts	↓ PDF

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D



Replaceable (LED only) light source by a professional



Replaceable control gear by an end-user



Photometric

Lighting type	Indirect
Light distribution	Asymmetric
CCT (K)	2700

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	100-240/24
Driver	Remote included
Dimming type	Electronic 24V
Cord length (mm)	1900
Plug type	Type G, Type A, Type C
Batteries inside	No
Charging min time	No

Spare Parts



F6605030
Taccia Small LED black base



F6606000
Taccia Small transparent diffuser
& reflector



RF24886
White reflector



RF3320100
Black plug assembly kit & 24V
driver



RF6605100
Jack plug with coaxial cable and
dimmer